PRODUCT SPECIFICATION GUIDE NEILPRYDE CRUISEPLUS ROLLER FURLING MAINSAIL Webbing attachment for Standard Features *Reefing buffer patch* flexible furling Head and Tack are webbed with rugged webbing Yachts over 30' l.o.a. will have a two-ply head and clew area of which each will be approximately 22% of the leech length ٠ Challenge Sailcloth High Modulus fabrics ٠ Clew fitted with Roller Block AND safety ring, with webbing protected by uv cover ٠ All seams will have 2 to 3 rows of 3-step stitching, depending on size ٠ Patches Radail style with reefing "buffer" patches at Head and Tack with reefing marks at tack ٠ Polyester or Spectra Leechlines Draft (trim) stripe and Insignia (choice of colours) ٠ Tell-tails Heavy Duty sailbag 2 or 3 rows of contrasting 3-U.V. sacrificial cover on both sides of step stitching and internal leechline chafe guard exposed clew **Optional Features** Seamkote Sail Numbers **Tradewinds Specifications** 2- ply clew with U.V. cover on both sides, radial

Quality, Service, Value

- Every sail we build comes with the assurance of a two year warranty of quality, service and value.
- If you ever need service, our consultants will direct you to the nearest of our worldwide network of Service lofts.
- No matter where in the world your sailing takes you, we are there to help.

patching, and safety ring

For further information, contact your Neil Pryde consultant by dialing 1-203-874-6984 or http://www.neilprydesails.com

Copyright Neil Pryde Sails Int. 2002 Oct-01

Drawings and type may describe features not applicable to all sizes of sails. Our ongoing development program may change features and specifications without notice.