


Standard Features

- ◆ Vertical aligned battens provide improved aerodynamics and increased sail area
- ◆ Head and Tack with flexible webbing attachments
- ◆ Clew fitted with Roller Block with webbing protected by U.V. material
- ◆ Pressed safety clew ring
- ◆ All seams will have 2 to 3 rows of 3-step stitching, depending on size
- ◆ Patches block style with reefing "buffer" patches at Head and Tack
- ◆ Polyester Leech and foot lines
- ◆ Tell-tails
- ◆ Heavy Duty sailbag
- ◆ U.V. sacrificial cover on both sides of clew

Webbing attachment for flexible furling



2 or 3 rows of contrasting 3-step stitching and internal leechline chafe guard

Optional Features

- ◆ Sail numbers
- ◆ Draftstripes

U.V. Cover on both sides of clew

Pressed safety ring

Quality, Service, Value

- ◆ Every sail we build comes with the assurance of a two year warranty of quality, service and value.
- ◆ If you ever need service, our consultants will direct you to the nearest of our worldwide network of Service lofts.
- ◆ No matter where in the world your sailing takes you, we are there to help.
- ◆ For further information, contact your Neil Pryde consultant by dialing 1-203-375-2626 or <http://www.neilprydesails.com>